

The Tasuma Trophy Series - SAM 35 RC Power Duration Rules 2014

This is a traditional free flight power duration type competition for vintage and classic era models but with the use of RC to enable thermal hunting and to land back within the field. Engine types are restricted to limit power and cost and the engine run time is varied according to engine size and type of model. Equivalent electric propulsion can be used. The intention is that a wide variety of vintage and classic 'competition' and 'sport' type models should be competitive.

Competition procedure: the CD will specify the launch (or take-off) and landing areas depending on the conditions prevailing. 3 rounds will be flown to a 5 minute maximum followed by a fly-off if necessary. A helper is permitted for starting and launching. In the event of an engine over-run or a flight of less than 1 minute, a single 'no flight' is permitted in each of the preliminary rounds. Landing outside of the specified area results in a zero score.

Multiple entries: are accepted if for different models but only the results from one model may be carried forward from the rounds and count toward the overall results.

Model eligibility: designs must have been flown, published or kitted by 1st January 1961. Construction must follow the original plan although substitution of materials, local strengthening, and adaptation for the engine used or electric propulsion and for RC are permitted. Scaling is permitted with appropriate changes to material sizes and rib spacing but all outlines and sections must remain in proportion.

Radio: must be 2.4Ghz.

Power bands and engine run times:

Power band	(A)	(B)	(C)
IC engine capacity	Up to 1cc	Up to 3.5cc	Up to 10.5cc
Electric power	Up to 100 watts	Up to 250 watts	Up to 650 watts
'Competition' models	25 secs run time	20 secs run time	15 secs run time
'Sports' models	30 secs run time	25 secs run time	20 secs run time

In the event of adverse flying conditions: the CD may proportionately reduce the engine run times, the 'no-flight' time and the maximum.

IC engines: only plain bearing non-schneurle 2 stroke engines are permitted (with the exception of the single bearing PAW 06 diesel because of the difficulty of getting decent alternative 1cc engines at reasonable cost). 4 stroke engines (not supercharged) are permitted in power band (C) for 'sports' models and for vintage 'competition' models (vintage designs must have been flown, published or kitted by 1st January 1951).

Electric propulsion: the wattage is that measured between the battery and the ESC when run on the ground with the flight propeller and a fully charged battery. Folding propellers are not permitted.

'Competition' and 'sports' models: designs deemed to be 'competition' models are the high performance types, typically but not exclusively of the pylon layout. 'Sports' models are lower performance types, typically but not exclusively of the cabin layout. Some cabin models, such as many of the PAAloaders, are high performance 'competition' types whereas some non-cabin models, such as the Simplex, are deemed to be lower performance 'sports' models. Common sense will apply and models may be reclassified in the light of experience. Those considering building a 'marginal' model should consult the RC Secretary for a ruling. If necessary the CD will adjudicate on the day.